



NATURES OWN LUBRICATION & CORROSION PROTECTION

USER GUIDE

MARINE COATING

PREPARATION:

ALL EQUIPMENT, WHICH HAS BEEN IN SEAWATER, SHOULD FIRST BE WASHED DOWN WITH LIQUID CHLORINE (3:1).

ALL BOAT HULLS MUST BE WASHED DOWN WITH LIQUID CHLORINE (3:1) TO KILL ANY MICROSCOPIC SPORE.

FIBREGLASS HULLS

For “New” or previously untreated hulls we recommend the use of a Gelcote sealer if one has not been applied previously, prior to the application of our “Coating”. Surface must be CLEAN and DRY.

Woolube Ozspray should not affect the Gelcote sealer used on fiberglass hulls and there have been no reported instances where *Woolube Ozspray* has reacted with a Gelcote sealer coating. If you are unsure about applying *Woolube Ozspray* it is recommended that an inconspicuous section be coated to test for reactivity. If reaction occurs please do not apply *Woolube Ozspray*.

ALUMINIUM HULLS

Surface must be CLEAN and DRY. If heavy oxidation exists, remove with aluminium cleaner, and then apply our “*Ozspray*”.

PREVIOUSLY ANTI-FOULED HULLS

Remove marine growth and loose anti-foul particles thoroughly. Surface must be CLEAN and DRY before application of our “Coating”.

PO BOX 167 Berowra Heights, NSW 2082
Phone: 1300 664 663 Facsimile: 02 9456 6272
Email: info@woolube.com.au



APPLICATION:

HULLS

OZSPRAY Coating can be applied by:

- (a) Sprays (including airless)
 - (b) Roller or brush
- Generally 1 or 2 coats are sufficient.
Always allow evaporation time between coats and before launching.
Remember OZSPRAY always remains tacky until submerged.

OTHER APPLICATIONS

- Outboard legs
- Stern Drives
- Sail Drives
- Log Spigots
- Bow Thrusters
- Intake Pick-up Grates
- Buoys

As usual, surface must be **CLEAN** and **DRY**
Apply "Coating" as for **HULLS**.

GROUND TACKLE & PROPS

Use **WOOLUBE**.
See the User Guides or **ASK US NOW!**

REAPPLICATION

Clean off with steam cleaner or hot pressure wash. Surface may be cleaned by using Surface Prep or by hand scrubbing with hot water above 60°C.

When **CLEAN** and **DRY**, reapply as per instructions.

MAINTANANCE

All moored hulls **MUST** be visually inspected, and the hull wiped down every 4 – 6 weeks if required.

PO BOX 167 Berowra Heights, NSW 2082
Phone: 1300 664 663 Facsimile: 02 9456 6272
Email: info@woolube.com.au



BENEFIT SUMMARY

OZSPRAY is the ideal marine coating because of its proven ability to resist acid etching, i.e. barnacles. Subsequent reapplication requires no special hull treatment such as sanding/grinding etc.

Slipway or hardstand time will be greatly reduced due to the saving in preparation and spray application time.

OZSPRAY Marine Coating will virtually eliminate electrolysis – a little spray will stop this expensive killer

OZSPRAY will not totally stop bacterial attachments, but it drastically reduces this ongoing process and saves our waterways from the dreadful and toxic cocktails caused by some traditional anti-fouls.

PO BOX 167 Berowra Heights, NSW 2082
Phone: 1300 664 663 Facsimile: 02 9456 6272
Email: info@woolube.com.au