

## Ozseal Lanolin Corrosion Protector

### PRODUCT OVERVIEW

**Ozseal** is a high-performance lanolin fluid film that forms a low tack coating to resist dust build up while forming a moisture tight seal around substrates that will resist alkali, acid, atmospheric moisture, and salt corrosion.

**Ozseal** is highly robust when and dry will not flake or chip and retains its elasticity making it suitable for car underbodies as a corrosion protector.

### FEATURES AND BENEFITS

- The ultimate in Lanolin barrier film coating for exterior and interior corrosion protection.
- Quick to dry and forms a low tack moisture tight seal that resists acids, fertilizer, moisture ingress and salt corrosion.
- Will not flake or chip. Protects metals and all alloy surfaces.
- High wash out water resistance.
- Long lasting robust protection in highly corrosive environments.
- Environmentally Safe, Eco-Friendly.
- Suitable for applications around waterways and sensitive environments.
- Dielectric test to 40kV.
- Protection of Spare Parts during storage.
- Suitable for 4WD offroad vehicles, Agricultural Vehicles (Harvesters, Trucks, Trailers and Bikes etc.).
- Displaces moisture, lubricates all surfaces, and will not wash off.
- Environmentally friendly and Biodegradable.

### PREPARATION

- For the best results apply to a clean, dry surface.
- Ensure the product is well mixed before using (shake or stir).
- Remove all sources of ignitions, voltage, and flame before use.
- Light oils should be removed before applying Ozseal on machined parts.
- Where short term mothballing of equipment is required, a final clean with a powerful degreaser such as Woolube Citra-Blitz before applying Ozseal corrosion Protector is recommended.

### COMMON USES

- Protecting exterior surfaces from surface rust and
- Penetrates rusted surfaces to free nuts and tools.
- Lubricates exterior equipment, chain and blocks.
- Moisture proofs multi-pin plugs and connectors.
- Protects electrical components, switchgear, and circuit boards.
- Ideal for marine applications to protect against salt spray.
- Anti-spatter protection when welding.
- Lubricates rubber hoses, o-rings, linkages, pivot pins and bushes.
- Protects metal fastenings and fittings from corrosion

### APPLICATION GUIDE

- Apply using spray or brush. Apply 2 coats with 6 hours.
- Reapplication is recommended every 3-6 months if external.
- Reapplication is not required if stored out of direct sunlight (e.g. in a warehouse).
- Good visual inspection is recommended regularly where products are stored or operating in a corrosive environment.
- Do a reapplication when required during service intervals.
- Always allow it to dry before additional reapplication.
- Exterior: Reapplication is recommended every 3 months or when further protection is required.  
Interior: Reapplication is not required if stored out of direct sunlight (i.e. in a warehouse).

Lanolin Technologies Pty Ltd

ABN: 82 627 249 629

100 Mitchell Road, CARDIFF NSW

2285 Phone: 1300 664 663

[www.woolube.com.au](http://www.woolube.com.au)



## Ozseal Lanolin Corrosion Protector

<b>Appearance</b>	Transparent dark brown mobile fluid
<b>Boiling Point Range</b>	>120
<b>Flash Point (°C)</b>	>80
<b>Specific Gravity (g/ml)</b>	@15°C) 0.90
<b>pH</b>	Neutral
<b>Viscosity @ 20°C</b>	35 cSt
<b>Solubility in Water</b>	Immiscible
<b>VOC</b>	Low
<b>Odour</b>	Low wool grease odour
<b>Storage</b>	Classed as non-dangerous - Store in a cool, dry place Shelf life - indefinitely when kept sealed and in reasonable conditions
<b>Pack Size - Item Codes</b>	300gm Aerosol - OS300C 750ml Trigger Bottle - OS750mL 5 Litre Jerry - OS5L 20 Litre Cube - OS20L 200 Litre Drum - OS200L

### SAFETY DATA SHEETS

For safe handling of this product, please consult the Safety Data Sheet (SDS).

Safety data sheets are available from our website [www.woolube.com.au](http://www.woolube.com.au)

### DISCLAIMER

Data given here is for information only: not certified product claims: based on one sample only: based on lab conditions: subject to change. Product supplied may show variation. There are many factors outside our control or knowledge which effect the use and performance of our products, for this reason it is given without responsibility.

### Lanolin Technologies Pty Ltd

ABN: 82 627 249 629

100 Mitchell Road, CARDIFF NSW

2285 Phone: 1300 664 663

[www.woolube.com.au](http://www.woolube.com.au)

Issue Date: 12/2021

