

Ozspray General Purpose Lanolin Lubricant

PRODUCT OVERVIEW

Woolube Ozspray General Purpose lanolin lubricant is a sprayable form of **Woolube** Grease which dries to a fine grease film offering the same characteristics as the grease as well as providing an excellent fluid displacement, penetrant, and lubricant in one multi-purpose product.

FEATURES AND BENEFITS

- Displaces moisture from surfaces, protecting them from corrosion.
- Penetrates metal surfaces preventing wear and providing extended protection.
- Penetrates seized parts for easing release.
- Long-lasting lubrication for all moving parts.
- Protects equipment from atmospheric acid and salt corrosion.
- Protects electrical applications and appliances from corrosion.
- Resists breakdown in high temperatures and temperature variation.
- Non - Conductive / Di electric up to 70kV.
- Food Safe and resistant to wash off.
- Eco-friendly, can be used around waterways in all environments.
- Environmentally friendly and Biodegradable.

PREPARATION

- Best applied to dry, clean surfaces
- Use Woolube Citra Blitz degreaser to clean surface prior to application or to remove grease

COMMON USES

- Protecting exterior surfaces from surface rust and
- Penetrates rusted surfaces to free nuts and tools.
- Lubricates exterior equipment, chains and blocks.
- Moisture proofs multi-pin plugs and connectors.
- Protects electrical components, switchgear and circuit boards.
- Ideal for marine applications to protect against salt spray.
- Anti-spatter protection when welding.
- Lubricates rubber hoses, O-rings, linkages, pivot pins and bushes.
- Protects metal fastenings and fittings from corrosion.

APPLICATION GUIDE

- Shake the container to ensure product is mixed correctly. Colder climates will require little extra stirring or shaking.
- Ozspray General Purpose Lanolin Lubricant can be applied via spray, brush, roller, or lamb's wool applicator.
- Coverage is approximately 20m² per litre. Only one good coat is required.
- When applying to objects via spray, hold 30cm away from object. Start from the top and coat evenly from one side to the other.
- Reapplication in exterior applications is recommended after every 6-8 months.

Lanolin Technologies Pty Ltd

ABN: 82 627 249 629

100 Mitchell Road, CARDIFF NSW

2285 Phone: 1300 664 663

www.woolube.com.au



Ozspray General Purpose Lanolin Lubricant

Appearance	Transparent honey coloured mobile fluid
Boiling Point Range	>150
Flash Point (°C)	80
Specific Gravity (g/ml)	@15°C) 0.88
pH	Neutral
Viscosity @ 20°C	25 cSt
Solubility in Water	Immiscible
VOC	Low
Odour	Low
Storage and Handling	Aerosols classed as Dangerous Goods Flammable Goods - DG Class 2.1 UN 1950. All other packs classified as NON-Dangerous Goods. Store in a cool well-ventilated place. Keep out of reach of children. Shelf Life - 5 years if kept sealed in a controlled temperature enclosed environment < 25°C.
Pack Size - Item Codes	60gm mini Aerosol - OZ60C 300gm Aerosol - OZ300C 750ml Trigger Bottle - OZ750mL 5 Litre Jerry - OZ5L 20 Litre Cube - OZ20L 200 Litre Drum - OZ200L

SAFETY DATA SHEETS

For safe handling of this product, please consult the Safety Data Sheet (SDS).
Safety data sheets are available from our website www.woolube.com.au

DISCLAIMER

Data given here is: for information only; not certified product claims; based on one sample only; based on lab conditions; subject to change. Product supplied may show variation. There are many factors outside our control or knowledge which effect the use and performance of our products, for this reason it is given without responsibility.

Lanolin Technologies Pty Ltd

ABN: 82 627 249 629
100 Mitchell Road, CARDIFF NSW
2285 Phone: 1300 664 663
www.woolube.com.au

Issue Date: 12/2021

